



CORDLESS BATTERY CRIMPING TOOLS

AEP-185 SERIES

AEP-185, 6 tons output, Weight: 4kgs, Crimping range: 6-185mm²

Model	Output	Head Rotation	Application	Standard Dies	Crimping Range Supported	Dimension	Weight	Remark
AEP-185	6 tons	360°	Cable lug hexagon crimping	Standard die set (total 6pcs) 10-16/ 25-35/ 50-70/ 95-120/ 150/ 185-6mm ² (i.e. B1801-B1806/ R18 type)	6-185mm² AWG10-350MCM crimping range	385(L)x290 (W)x75(H)mm	4kgs excludes battery	Flip-latch type, auto-release version



AEP-240

AEP-300

AEP-240&300 SERIES

AEP-240 & 300, 6 tons output, Weight: 4.2 & 4.8 kgs, Crimping range: 10-240mm² & 6-300mm²

Model	Output	Head Rotation	Application	Standard Dies	Crimping Range Supported	Dimension	Weight	Remark
AEP-240	6 tons	360°	Cable lug hexagon crimping	Standard die set (total 7pcs) 10-16/ 25-35/ 50-70/ 95-120/ 150/ 185/ 240mm ² (i.e. B8001-B8007/ R19 type)	10-240mm² AWG8-600MCM crimping range	400(L)x295 (W)x75(H)mm	4.2kgs excludes battery	Flip-latch type, auto-release version
AEP-300	6 tons	360°	Cable lug hexagon crimping	Standard die set (total 7pcs) 70/95/120/150/185/240/300mm ² (i.e. B2270-B22300/R22 type)	6-300mm² (AWG10-600MCM)	467(L)x323 (W)x75(H)mm	4.8kgs excludes battery	Auto-release version



AEP-3001 SERIES

AEP-3001, 12 tons output, Weight: 6.6kgs, Crimping range: 6-400mm²

Model	Output	Head Rotation	Application	Standard Dies	C-Jaw Opening	Crimping Range Supported	Dimension	Weight	Remark
AEP-3001	12 tons (120-130kN)	360°	Cable lug hexagon crimping	Standard die set (total 10pcs) 35/50/ 70/95/120/150/185/240/300/400mm ² (i.e. B3035-B30400/R30 type)	30mm	6-400mm² (AWG10-750MCM)	467(L)x323 (W)x88(H)mm	6.6kgs excludes battery	Auto-release version



AEP-6301 SERIES

AEP-6301, 18 tons output, Weight: 7.3kgs, Crimping range: 630mm²

Model	Output	Head Rotation	Application	Standard Dies	Crimping Range Supported	Dimension	Weight	Remark	
AEP-6301	18 tons	360°	Cable lug hexagon crimping	Standard die set (total 12pcs) 35/50/70/95/ 120/150/185/240/300/400/500/630mm ² (i.e. B3035-B30400, B63500, B63630/R30 type)		Max. 630mm² crimping range	467(L)x323 (W)x90(H)mm	7.3kgs excludes battery	Auto-release version