

CUTTERS



REMOTE HYDRAULIC CUTTING HEAD AWC & AWR SERIES

FEATURES

- Single acting, spring-return on all models, except AWR1250.
- Guillotine action for efficient operation. Lifting handles on larger models
- Carrying bag included for easy carrying and tool protection.
- Ideal for use with most pumps featuring 3-way valve or dump valve and 10,000 psi pressure rating (except AWR1250, which requires 4-way valve). AR400 coupler and dust cap included on all models.

Model Number	Cutter Head Operation	Capacity (ton)	Oil Cap. (cc)	Steel Wire Rope, Hemp-core or IWRC 6x7 6x12 6x19	Round Bar				Wire Strand				Cable		Length (in)	Wt. (lbs)	Replacement Blade Kit Numbers
					Copper Wire or Bar	Aluminum Wire or Bar	Soft Steel Bolts	Reinforcing Bar	Bare Copper Wire Strands	Bare Aluminum Wire Strands 6x7	ACSR	Guy Steel Wire Strands 1x7 1x19	Telephone Cable CPP	Underground Cable (Power)			
AWC750*	Single-acting	4	19.6	0.63	0.75	0.75	0.75	0.50***	0.75	0.75	0.75	0.63	☆	☆	5.00	7	ACB750
AWC1250*		20	134.3	1.25	1.25	1.25	1.25	1.00	1.25	1.25	1.25	0.88	☆	☆	11.00	25	ACB1250
AWC2000		13	119.6	1.00	1.25	1.25	0.88	☆	2.00	2.00	2.00	0.75	☆	☆	15.00	23	ACB2000
AWC3380		3	65.5	☆	☆	☆	☆	☆	3.00	3.00	☆	☆	3.38	3.38	19.00	20	ACB3380
AWC4000		8	137.6	☆	☆	☆	☆	☆	3.50	3.50	☆	☆	4.00	4.00	24.00	32	ACB4000
AWR1250	D/A **	20	122.9	1.25	1.25	1.25	1.25	1.00	1.25	1.25	1.25	0.88	☆	☆	16.50	26	ACB1250



HYDRAULIC CUTTERS SELF-CONTAINED AHC SERIES Capacity: 3 to 20 Tons

FEATURES

- Rotating heads for operator convenience. Guillotine action (except AHC1000) for efficient operation. Carrying bag included for easy carrying and tool protection.
- Velcro straps to secure handles on larger models for easy transportation. Spring-return on all models. Lightweight, self-contained tool, can be used anywhere.

Model Number	Capacity (ton)	Steel Wire Rope, Hemp-core or IWRC 6x7 6x12 6x19	Round Bar				Wire Strand				Cable		Length (in)	Weight (lbs)		
			Copper Wire or Bar	Aluminum Wire or Bar	Soft Steel Bolts	Reinforcing Bar	Bare Copper Wire Strands	Bare Aluminum Wire Strands 6x7	ACSR	Guy Steel Wire Strands 1x7 1x19	Guy Steel Wire Strands 1x19	Telephone Cable CPP			Underground Cable (Power)	
AHC580	4	0.63	0.63	0.63	0.63	0.38	0.63	0.63	0.63	0.63	0.56	0.56	☆	☆	15.00	8
AHC750	4	0.75	0.75	0.75	0.69	0.50***	0.75	0.75	0.75	0.75	0.56	0.56	☆	☆	15.00	8
AHC1000*	20	☆	0.75	0.75	0.75	0.75	☆	☆	☆	☆	☆	☆	☆	☆	26.75	25
AHC1250	20	1.25	1.25	1.25	1.25	0.88	1.25	1.25	1.25	1.25	0.88	0.88	☆	☆	26.75	23
AHC1580	6	0.75	0.75	0.75	0.75	☆	1.50	1.50	1.50	1.50	0.63	0.63	☆	☆	22.00	15
AHC2000	13	1.00	1.25	1.25	0.88	☆	2.00	2.00	2.00	2.00	0.75	0.75	☆	☆	24.75	24
AHC3380	3	☆	☆	☆	☆	☆	3.00	3.00	☆	☆	☆	☆	3.38	3.38	26.00	22