

MANUAL HYDRAULIC CABLE CUTTERS

CUTTERS

AS-505 SERIES

AS-505 (Manual Type)
5 tons output / 6kgs / 520mm



Bare Strands



Lead Sheated Underground Cable



Communication Cable



| Model | Output | Bare Copper Wire Strand | Bare Aluminum Wire Strand | CCP & Lead-Sheathed Cable | Weight | Length |
|--------|--------|-------------------------|---------------------------|---------------------------|--------|--------|
| AS-505 | 5 tons | Max. O.D. 28mm | Max. O.D. 46mm | Max. O.D. 50mm | 6 kgs | 520mm |

ACPC-85A SERIES

ACPC-85A SERIES (Manual Type)
5 tons output / 7kgs / 695mm



Lead Sheated Underground Cable



PVC Sheated Underground Cable



Bare Strands



Communication Cable



| Model | Output | Bare Copper Wire Strand | Bare Aluminum Wire Strand | CCP Cable | Underground Cable | Weight | Length | Remark |
|----------|--------|-------------------------|---------------------------|----------------|-------------------|--------|--------|-----------------|
| ACPC-85A | 5 tons | Max. O.D. 28mm | Max. O.D. 38mm | Max. O.D. 85mm | Max. O.D. 50mm | 7 kgs | 695mm | Free pin design |

AS-40 SERIES

AS-40 (Manual Type)
8 tons output / 6kgs / 560mm
Double-stage hydraulic design



Soft Copper Bar



Soft Aluminum Bar



Soft Steel Bar



Wire Rope



Steel Wired Armoured Cable



Bare Strands



| Model | Output | Hemp-core wire rope 6x7 | Hemp-core wire rope 6x12 | Hemp-core wire rope 6x19 | Soft Copper & Aluminum Round Bar | Soft steel round bar (below SS41) | Bare copper & Aluminum wire strand | Weight | Length | Remark |
|-------|--------|-------------------------|--------------------------|--------------------------|----------------------------------|-----------------------------------|------------------------------------|--------|--------|-------------------------------|
| AS-40 | 8 tons | Max. O.D. 22mm | Max. O.D. 25mm | Max. O.D. 25mm | Max. O.D. 25mm | Max. O.D. 16mm | Max. O.D. 40mm | 6 kgs | 560mm | Double-stage hydraulic design |

AS-85YFR SERIES

AS-85YFR (Manual Type)
12 tons output / 11.15kgs / 780mm
With FRP insulated handle, Scissor-open type



CU/AL Cable



Steel Wired Armoured Cable



Lead Sheated Underground Cable



| Model | Output | Copper & Aluminum cable | Lead-sheathed cable | Armored underground cable | Weight | Length | Remark |
|----------|---------|-------------------------|---------------------|---------------------------|-----------|--------|--|
| AS-85YFR | 12 tons | Max. O.D. 85mm | Max. O.D. 85mm | Max. O.D. 85mm | 11.15 kgs | 780mm | With FRP insulated handle, Scissor-open type |

AWR-25 & 32 SERIES

AWR-25 & AWR-32 (Manual Type)
8 & 18 tons output / 4 & 11kgs / 426 & 720mm



Soft Copper Bar



Soft Aluminum Bar



Wire Rope



Bare Strands



| Model | Output | Hemp-core wire rope 6x7 | Hemp-core wire rope 6x12 | Hemp-core wire rope 6x19 | Soft Copper & Aluminum Round Bar | Soft steel round bar (below SS41) | Bare copper & Aluminum wire strand | Armored Underground Cable | Weight | Length |
|--------|---------|-------------------------|--------------------------|--------------------------|----------------------------------|-----------------------------------|------------------------------------|---------------------------|--------|--------|
| AWR-25 | 8 tons | Max. O.D. 18mm | Max. O.D. 25mm | Max. O.D. 25mm | Max. O.D. 25mm | - | Max. O.D. 25mm | - | 4 kgs | 426mm |
| AWR-32 | 18 tons | Max. O.D. 32mm | Max. O.D. 32mm | Max. O.D. 32mm | Max. O.D. 32mm | Max. O.D. 25mm | Max. O.D. 32mm | Max. O.D. 32mm | 11 kgs | 720mm |