

HYDRAULIC CYLINDER MULTI STAGE CYLINDER

ARCD SERIES

Capacity: 5-65 TON
Stroke : 60-155
700 Bar (10,000 psi)

FEATURES

- Multi-stage design for maximum stroke in a small space to lifting.
- Piston hard chrome plating to prevent scratches and corrosion.
- Single Acting, Load return.
- Each model has 3/8" (76.2mm) NPT coupler and dust.
- High temperature paint, wear resistance, corrosion resistance.



Model Number	Capacity (tons)		Stroke (Each Stage) (mm)	Collapsed Height (mm)	Outside Dia. (mm)	Working Pressure (bar)
	1st Stage	2nd Stage				
ARCD-13T-5T-60	13	5	60	150	68	700
ARCD-22T-10T-75	22	10	75	172	86	700
ARCD-30T-10T-135	30	10	135	250	110	700
ARCD-40T-20T-75	40	20	75	175	112	700
ARCD-43T-16T-150	43	16	150	280	125	700
ARCD-65T-30T-150	65	30	150	265	146	700

HYDRAULIC CYLINDER TWIN STAND

ASG SERIES

100x2 TON
Stroke : 32-50

FEATURES

- The single acting twin stand hydraulic cylinder can reduce the outside diameter size, but the capacity is not change.
- The cylinder has lock nut on the piston
- The cylinder is suitable for narrow space.
- Suit for front and rear left and right adjustments.



Model Number	Capacity	Stroke	Collapsed Height	Outside Dia.	Piston Rod Dia.	Working Pressure
	tons	(mm)	(mm)	(mm)	(mm)	(bar)
ASG-100T-32	100 x 2	32	150	340x165	110	700
ASG-100T-50	100 x 2	50	250	330x134	66	700