

BATTERY HYDRAULIC PUMP



APMS-P5, APM-P5 BATTERY HYDRAULIC PUMP



APML-P1 BATTERY HYDRAULIC PUMP



APML-P2 BATTERY HYDRAULIC PUMP

Model Number	Voltage	Battery	Acting Pressure	Pressure	Max. pressure 700kgF/cm ²	Min. pressure 20kgF/cm ²	Reservoir Capacity	Weight	Dimension	Accessory	Remark
APM-P5	18VDC	18V Li-Ion	Single	700kg F/cm ²	270c.c./min. oil speed	1600c.c./min. oil speed	1.4 Liter	6.5kgs	330(L)x271 (W)x155(H)mm	1 Pcs charger 1 Pcs battery 1 Pcs 1.8M hose 1 Pcs remote control 1 Pcs shoulder bag	-
APMS-P5	18VDC	18V Li-Ion	Single	700kg F/cm ²	270c.c./min. oil speed	1600c.c./min. oil speed	1.4 Liter	6.5kgs	330(L)x271 (W)x155(H)mm	1 Pcs charger 1 Pcs battery 1 Pcs 1.8M hose 1 Pcs remote control 1 Pcs shoulder bag	Reminder & buzz warning system for temperature, voltage, pressure, power & record. Pressure hold
APML-P1	14.4VDC	14.4V Li-Ion	Single	700kg F/cm ²	150c.c./min. oil speed	505c.c./min. oil speed	0.55 Liter	8kgs	355(L)x260 (W)x160(H)mm	1 Pcs charger 1 Pcs battery 1 Pcs 1.8M hose 1 Pcs remote control	-
APML-P2	28.8VDC	14.4V Li-Ion	Single	700kg F/cm ²	300c.c./min. oil speed	1800c.c./min. oil speed	1.7 Liter	16.3kgs	400(L)x220 (W)x180(H)mm	1 Pcs charger 2 Pcs batteries 1 Pcs 1.8M hose 1 Pcs remote control	-



PUNCHING

AMAP-10 REMOTE HYDRAULIC PUNCH HEAD KIT WITH PUMP

Model Number	Punch Head	Punch dies x 10 sizes	Draw x 3 sizes	Spacer x 3 sizes	Standard hand pump	For stainless steel plate	For galvanized steel plate	Application
AMAP-10	AMAP10-H	Ø 21.8-115.5mm (1/2"-4")	3/8" & 3/4" & 1"	Ad20 & Ad34 & Ad44	H-B with 1.8M Hose	Max. Thickness 1.6mm (Gauge 16)	Max. Thickness 3.2mm (Gauge 11)	For Panel & Switch Board